



# PHOS-CHEK®

Fire Retardant, Class A Foam & Gel



## ICL Performance Products LP

www.phoschek.com

## PHOS-CHEK® AquaGel-K Fire Suppressant Gel

### Uses:



PHOS-CHEK AquaGel-K is a fire suppressant gel approved by the USDA Forest Service as a “water enhancer”. AquaGel-K can be applied by all types of application equipment used in direct fire suppression, for indirect suppression as a protective barrier and a medium-term fire retardant and for the protection of structures exposed to an advancing fire.

PHOS-CHEK AquaGel-K water enhancing gel is used for wildland fire control in forest, brush or grassland, direct suppression of structural fires and for exposure protection. Functionally, PHOS-CHEK AquaGel-K absorbs water many times its own weight and forms a gel producing increased droplet sizes that reduce drift and evaporation when dropped aerially. In many applications the gel forms a cohesive layer which acts as a vapor barrier and prolongs the effectiveness of the water.

### Description:

AquaGel-K is a dry powder that when added to water in very low concentrations (0.1 to 1.2 percent by weight), rapidly absorbs water to produce a gel whose consistency (viscosity) depends on the selected concentration. The dry powder is self dispersing in many applications or it can be easily mixed by in-line induction or by simple circulation.

PHOS-CHEK AquaGel-K is environmentally friendly and contains no polyacrylamide, NPE, oils or solvents. AquaGel-K requires no special expensive chemical for wash-down or clean up when used in structural applications.

### Typical Analysis:

Color:	Uncolored (AquaGel-K) Fugitive (AquaGel-K liquid color additive)
Mix Ratio / Use Levels:	0.1 to 1.2 percent by weight when mixed with water <i>(desired mix ratio can be adjusted depending on application)</i> Backpacks pumps: 0.1 percent by weight or less Engines / Pumpers: 0.2 to 0.4 percent by weight Helicopters / Air-Tankers: 0.4 to 0.8 percent by weight
Density:	8.34 lbs per US gallon <i>(when mixed with water at use levels 0.1 to 1.2 %)</i>
Viscosity:	1-20,000 centipoise (cP); see chart viscosity use-levels

### Packaging:

PHOS-CHEK AquaGel-K is available in 1212 lb. bulk bags, 35 lb. bags, 24 lb. pails, 10 lb. pails and mini pouches.  
Fugitive Color is available in 5 gal. pails, drums and semi-bulk tote bins.

### Shipping Classification:

Fire Extinguisher Compound NOIBN



## PHOS-CHEK® AquaGel-K Fire Suppressant Gel

### Handling

### Precautions:

FOR DETAILED SAFETY INFORMATION PLEASE REFER TO THE MSDS.

MAY CAUSE IRRITATION TO EYES; CONSIDERED PRACTICALLY NO IRRITATION TO SKIN.

PRECAUTIONARY MEASURE AND FIRST-AID HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES. THESE PRACTICES INCLUDE AVOIDING UNNECESSARY CONTACT AND REMOVAL OF THE MATERIAL FROM THE EYES, SKIN AND CLOTHING.

EYE PROTECTION: As a good industrial practice, the use of chemical goggles is recommended. Eye flushing equipment should also be available.

SKIN PROTECTION: Wear protective gloves to minimize skin contact. Wash hands and contaminated skin after handling.

RESPIRATORY PROTECTION: None required.

IF IN EYES: Flush with plenty of water.

Notice: Although the information and recommendations set forth (herein thereafter "Information") are presented in good faith and believed to be correct as of the date hereof, ICL Performance Products LP makes no representations or warranties as to the completeness or accuracy thereof. Information is supplied upon the conditions that the persons receiving same will make their own determination as to the suitability for their purposes prior to use. In no event will ICL Performance Products LP be responsible for damages of any nature whatsoever resulting from the use of or reliance upon Information or the product to which the Information refers. Nothing containing herein is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent, and ICL Performance Products LP makes no representation or warranty, express or implies, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS.

For more information, contact any of our worldwide wildfire offices or visit us at [www.phoschek.com](http://www.phoschek.com):

United States	Canada	Europe	Australia
ICL Performance Products LP	ICL Performance Products	Biogema	Phoz-Chem Pty Ltd.
810 E. Main St.	Canada LTD	415, rue Armand-Pole	P.O. Box 2034
Ontario, CA 91761	3060 Airport Road	d'Activities	Templestowe Hts. Vic 3107
Tel (800) 682-3626	Kamloops, BC	13852 Aix-en-Provence Cedex 3	Australia
(909) 983-0772	Canada, V2B 7X2	France	Tel 61 3 9848 1111
24 Hrs (909) 946-7371	Tel (800) 665-2535	Tel (0) 4 42 24 45 08	Fax 61 3 9848 2711
Fax (909) 984-4770	(250) 554-3530	Fax (0) 4 42 24 29 98	
	Fax (250) 554-7788		